

Architects and Engineers Specification

Model 293-001 Wall Mount Emergency Telephone

The phone shall operate on a standard analog phone line. It shall be solely powered from the phone line and does not require a battery or external power source. The phone shall be rated for outdoor installation. The phone shall be auto-dial operation and shall be capable of automatically answering incoming calls.

Calls shall be initiated by using the **HELP** button. The **HELP** button shall always override all other operations to auto-dial the pre-programmed number immediately. When calls are connected, communication shall be hands-free, speakerphone operation. The phone shall be compliant to Americans with Disabilities Act (ADA) and provide the following features:

- Visual indicator when the call is received
- Phone location identification
- Call disconnect control from the called party
- **HELP** push-button with Braille tag and a large red “palm” button for easy activation. Push-buttons that do not provide a tactile feel when activated will not be acceptable.

Speaker volume sensitivity level shall be adjustable. The phone shall provide an auxiliary switch for activation of peripheral equipment when emergency calls are in progress.

The phone shall store three telephone numbers associated with the **HELP** button. If the first number dialed is busy or does not answer, the second and third numbers shall be dialed as required. The phone shall attempt to call each number three times.

The phone shall contain a microprocessor and non-volatile memory for storage of its programmable parameters. A customer-configurable password protection feature shall prevent unauthorized tampering. The phone shall be capable of local and remote programming. Local programming shall be accomplished using the keypad. Remote programming shall be accomplished by calling from another telephone and using DTMF tones. The phone shall have the following standard features:

- Auto-dial Numbers (24 digit capacity)
- Password (4 digits)
- Telephone line disconnect method (loop current, push-button, time-out, or dial tone)
- Silent Monitoring Feature (on/off)
- Local audible ringing (on/off)
- ADA Features (on/off; phone ID - 3digits).

The phone shall be weatherproof rated NEMA 3R with an operating temperature range of -40°C to $+60^{\circ}\text{C}$ and relative humidity to 95% non-condensing. Phone shall be a surface mount design with 9.5”x 8”x 3.8” (HxWxD, Valox housing, high-impact anti-corrosive polyester enclosure resistant to thermal degradation and immune to chemicals, solvents and salts. housing. A protective inner screen shall cover microphone and speaker openings on the front panel. The color shall be safety yellow. All mounting hardware shall be tamper-resistant. .

Telephone shall be designed and developed by the manufacturer.

Telephone manufacturer shall be ISO 9001 Certified.

Architects and Engineers Specification

Phone shall be registered under FCC Regulations, 47 CFR, part 68 and comply with UL/CSA 60950.

Telephone shall be manufactured by **GAI-Tronics Corporation as Model 293-001.**