S.M.A.R.T. Camera Phone

GAI-TRONICS®
A Hubbell Company

GAI-Tronics' Self Monitoring and Reporting Technology (S.M.A.R.T.) phones now offer a built-in camera option for increased security.

These S.M.A.R.T. Camera Phones offer all the standard features of our Self Monitoring and Reporting Technology (S.M.A.R.T.) phones with an added camera option. A built-in CCTV camera integrates audio and video into one package.

Model GTE04047 (293-003 style with Camera Option*)
- Bright Yellow High Impact Anti-Corrosive Valox Enclosure
- Red Emergency Push Button
- Surface-Mount or Pole-Mount (using 231-001 pole-mount kit)

Model GTE04048 (297-003 style with Camera Option*)
- Stainless Steel Flush Panel Construction
- Red Emergency Push Button
- Surface-Mount (using 236 series hooded enclosures) or Flush-Mount into GAI-TRONICS' Stanchions (234 or 234WM Series)

Model GTA05007 (298-003 style with Camera Option*)
- Stainless Steel Flush Panel Construction
- Red Emergency Button and Black Call Button with Braille Keypad for Local Calling
- Surface-Mount (using 236 series hooded enclosures) or Flush-Mount into GAI-TRONICS' Stanchions (234 or 234WM Series)

Model GTF04037 (294AL-003 style with Camera Option*)
- Bright Yellow Cast Aluminum Construction Enclosure
- Red Emergency Button and Black Call Button with Braille Keypad for local calling
- Surface-Mount or Pole-Mount (using 231-001 pole-mount kit)

Camera Features:
- Color camera 1/3" Super HAD CCD Sensor
- Employs Digital Processor (DSP) IC for image control
- Pixel Number: NTSC = 270,000 / PAL = 320,000
- High sensitivity, low smear, excellent anti-blooming and high Signal-to-Noise ratio
- Built-in functions: Auto Gain Control, Auto Electronics Shutter, and Auto White Balance
- Low power consumption: 120mA max. @ 12.0VDC
- Operating Temperature: -14 degrees F to +122 degrees F
- Standard BNC connection

* See -003 Series for detailed features and specifications.